

## PRODUCT SPECIFICATIONS:

<b>PILE CONTENT:</b>	100% Wool
<b>PILE WEIGHT:</b>	1627 gm/m <sup>2</sup> - 48 oz/yd <sup>2</sup>
<b>PILE HEIGHT:</b>	9 mm
<b>CARPET THICKNESS:</b>	11 mm
<b>MACHINE GAUGE:</b>	3.175 mm - 1/8"
<b>STITCH RATE:</b>	As required to provide a carpet of total pile mass, pile height and machine gauge as specified.
<b>WIDTH:</b>	3.66 metres
<b>PATTERN REPEAT:</b>	15 mm Width x 12.5 mm Length
<b>PRIMARY BACK:</b>	Heat Stabilised Woven Polypropylene
<b>SECONDARY BACK:</b>	Woven Jute/
<b>FIRE RATING:</b>	AS/ISO 9239.1:2003 (Available on request.)
<b>GRADING:</b>	Residential Extra Heavy Duty & Stairs Contract Medium Duty & Stairs
<b>ENVIRONMENTAL ACCREDITATION:</b>	Achieves Level 3 Certification under the ACCS Environmental Classification Scheme
<b>VOC EMISSIONS:</b>	Meets ACCS Environmental Classification Criteria
<b>WARRANTIES:</b>	15 Year Limited Residential Wear Warranty
<b>TOLERANCE:</b>	Manufactured to A.S. 1385 tolerances.
<b>INSTALLATION:</b>	To be laid in accordance with AS/NZS 2455.1:2007 Seam sealer must be applied to all seams (prior to joining).
<b>PATTERN MATCH:</b>	As with all tufted patterned carpets, exact pattern match, particularly in multiple width installations, cannot be guaranteed.
<b>SHADING:</b> (Permanent Pile Reversal)	Cut pile carpets have a propensity to shade. This is not a manufacturing fault further information can be obtained from the Carpet Institute of Australia leaflet.
<b>COUNTRY OF MANUFACTURE:</b>	Australia