

PRODUCT SPECIFICATIONS

Product Description	Textured Loop
Fibre	Nylon
Dye Method	Solution Dyed
Pile Weight	600 g/m ² - 18 oz
Machine Gauge	1/10"
Pile Height	High 5mm to Low 3mm
Total Thickness	7.5mm
Backing	Thermoplastic
Tile Size	500mm x 500mm
Installation Method	Quarter Turn



To be laid in accordance with AS/NZS 2455:2007(Parts 1 & 2)

Adhesive	Full floor coverage with low VOC pressure sensitive adhesive
Anti-Static Performance	AATCC 134 < 3.5kV
Dimensional Stability	< 0.2%
Fire Rating (AS/ISO 9239.1:2003)	Critical Radiant Flux 9.1 kW/m ²
Area of Use	Contract Heavy Duty & Stairs
Antimicrobial	Zinc Oxide antimicrobial treatment
Stain Resistance	The Solution Dyed Nylon fibres have an added sulfonated nylon copolymer that renders the fibre chemically inert to acid dyes and stains.
Soil Resistance	The Solution Dyed Nylon fibres are treated with an advanced non-oil based technology low soil finish.

ENVIRONMENTAL CREDENTIALS

Environmental Management System	ISO 14001:2004 certified (IQNet)
Indoor Air Quality	VOC emission rates meet the criteria for the Green Label Plus and the Green Building Council of Australia.
Recycled Content	Minimum 30% recycled yarn content
Product Stewardship	Victoria Carpets, in partnership with our customer, will on a project by project basis, enter into a contractual agreement to take back carpet at the end of its service life for reprocessing, reuse or recycling.

WARRANTIES

15 Years Limited Warranties for Wear, Colourfastness, Anti static, Dimensional Stability and Manufacturing Defects

Specifications are subject to and may change without notice. Colour variation may occur between sample and production due to dye lot tolerances.



ISO 9001:2008
ISO 14001:2004

Australia Freecall: 1800 136 040
New Zealand Freecall: 0800 445 510

Email: sales@victoria-carpet.com.au
www.victoriacarpets.com.au