

CROSSING IN TIME

PRODUCT SPECIFICATIONS

Product Description	Textured Loop
Fibre	nexlon™ Premium Nylon
Dye Method	Solution Dyed
Pile Weight	880 g/m ² - 26 oz
Machine Gauge	1/10"
Pile Height	High 5.5 mm to Low 4 mm
Total Thickness	8.5 mm
Backing	Recycled Tuntex Duraback
Tile Size	500mm x 500mm
Installation Method	Brick Quarter Turn



To be laid in accordance with AS/NZS 2455:2007(Parts 1 & 2)

Adhesive	Full floor coverage with low VOC pressure sensitive adhesive
Anti-Static Performance	AATCC 134 < 3.5kV
Dimensional Stability	< 0.2%
Fire Rating	AS/ISO 9239.1:2003
Area of Use	Contract Extra Heavy Duty & Stairs
Stain Resistance	stainShield treatment
Soil Resistance	SOIL GUARD treatment
Anti-Microbial	MicroShield
Odour Reducer	ecoFRESH


ENVIRONMENTAL CREDENTIALS

Environmental Management System	ISO 14001:2015 certified (IQNet)
Environmental Accreditation	Achieves Level 3 Certification under the ACCS Environmental Classification Scheme
Indoor Air Quality	VOC emission rates meet the criteria for the Green Label Plus and the Green Building Council of Australia.
Product Stewardship	Victoria Carpets, in partnership with our customer, will on a project by project basis, enter in to a contractual agreement to take back carpet at the end of its service life for reprocessing, reuse or recycling.

WARRANTIES

15 Years Limited Warranties for Wear, Colourfastness, Anti static, Dimensional Stability and Manufacturing Defects

Specifications are subject to and may change without notice. Colour variation may occur between sample and production due to dye lot tolerances.



Australia Freecall: 1800 136 040
New Zealand Freecall: 0800 445 510

Email: sales@victoriacarpets.com.au
www.victoriacarpets.com.au