

CROSSING IN TIME

PRODUCT SPECIFICATIONS

Product Description

Fibre

Dye Method

Pile Weight

Machine Gauge

Pile Height

Total Thickness

Backing

Tile Size

Installation Method

Textured Loop

nexlon™ Premium Nylon

Solution Dyed

880 g/m² - 26 oz

1/10"

High 5.5 mm to Low 4 mm

8.5 mm

Recycled Tuntex Duraback

500mm x 500mm

Brick Quarter Turn



To be laid in accordance with AS/NZS 2455:2007(Parts 1 & 2)

Adhesive

Anti-Static Performance

Dimensional Stability

Fire Rating

Area of Use

Stain Resistance

Soil Resistance

Anti-Microbial

Odour Reducer

Full floor coverage with low VOC pressure sensitive adhesive

AATCC 134 < 3.5kV

< 0.2%

AS/ISO 9239.1:2003

Contract Extra Heavy Duty & Stairs

stainShield treatment

SOIL GUARD treatment

Micro Shield

ecoFRESH

ENVIRONMENTAL CREDENTIALS

Environmental Management System

Environmental Accreditation

Indoor Air Quality

Product Stewardship

ISO 14001:2015 certified (IQNet)

Achieves Level 3 Certification under the ACCS Environmental Classification Scheme


VOC emission rates meet the criteria for the Green Label Plus and the Green Building Council of Australia.

Victoria Carpets, in partnership with our customer, will on a project by project basis, enter in to a contractual agreement to take back carpet at the end of its service life for reprocessing, reuse or recycling.

WARRANTIES

15 Years Limited Warranties for Wear, Colourfastness, Anti static, Dimensional Stability and Manufacturing Defects

Specifications are subject to and may change without notice. Colour variation may occur between sample and production due to dye lot tolerances.



Australia Freecall: 1800 136 040
New Zealand Freecall: 0800 445 510

Email: sales@victoriacarpets.com.au
www.victoriacarpets.com.au