

PRODUCT SPECIFICATIONS

Product Description	Multi Hi / Lo Loop
Fibre	nexlon™ Standard + Prisma Premium
Dye Method	Solution Dyed
Pile Weight	600 g/m ² - 18oz
Machine Gauge	1/12"
Pile Height	High 5mm - Low 3mm
Total Thickness	7.5mm
Backing	Recycled Tuntex Duraback
Tile Size	250mm x 1000mm
Installation Method	Various – refer to brochure
Adhesive	To be laid in accordance with AS/NZS 2455:2007(Parts 1 & 2)
Anti-Static Performance	Full floor coverage with low VOC pressure sensitive adhesive
Dimensional Stability	AATCC 134 < 3.5kV
Fire Rating (AS/ISO 9239.1:2003)	< 0.2%
Area of Use	Critical Radiant Flux 3.3 kW/m ²
Stain Resistance	Contract Heavy Duty & Stairs
Soil Resistance	STAINSHIELD™ treatment
	SOILGUARD™ treatment

ENVIRONMENTAL CREDENTIALS

Environmental Management System	ISO 14001:2015 certified
Indoor Air Quality	VOC emission rates meet the criteria for the Green Label Plus and Green Building Council.
Product Stewardship	Victoria Carpets, in partnership with our customer, will on a project by project basis, enter in to a contractual agreement to take back carpet at the end of its service life for reprocessing, reuse or recycling.

WARRANTIES

15 Years Limited Warranties for Wear, Colourfastness, Anti static, Dimensional Stability and Manufacturing Defects

Specifications are subject to and may change without notice. Colour variation may occur between sample and production due to dye lot tolerances.

Australia Freecall: 1800 136 040
New Zealand Freecall: 0800 445 510

Email: sales@victoriacarpets.com.au
www.victoriacarpets.com.au

