SKATE

VICTORIA CARPETS®
Established 1895

PRODUCT SPECIFICATIONS

Product Description	Textured Loop
Fibre	nexlon™ Standard + Prisma + Circular Premium with recycled content
Dye Method	Solution Dyed
Pile Weight	600 g/m² - 18oz
Machine Gauge	1/12“
Pile Height	High 4.5mm - Low 3mm
Total Thickness	7mm
Backing	Recycled Tuntex Duraback
Tile Size	500mm x 500mm
Installation Method	Monolithic Ashlar Brick Quarter Turn To be laid in accordance with AS/NZS 2455:2007(Parts 1 & 2)
Adhesive	Full floor coverage with low VOC pressure sensitive adhesive
Anti-Static Performance	AATCC 134 < 3.5kV
Dimensional Stability	< 0.2%
Fire Rating (AS/ISO 9239.1:2003)	Critical Radiant Flux 7.5 kW/m²
Area of Use	Contract Heavy Duty & Stairs
Stain Resistance	STAINSHIELD™ treatment
Soil Resistance	SOILGUARD™ treatment

ENVIRONMENTAL CREDENTIALS

Environmental Management System	ISO 14001:2015 certified
Indoor Air Quality	VOC emission rates meet the criteria for the Green Label Plus and Green Building Council.
Product Stewardship	Victoria Carpets, in partnership with our customer, will on a project by project basis, enter in to a contractual agreement to take back carpet at the end of its service life for reprocessing, reuse or recycling.

WARRANTIES

15 Years Limited Warranties for Wear, Colourfastness, Anti static, Dimensional Stability and Manufacturing Defects

Specifications are subject to and may change without notice. Colour variation may occur between sample and production due to dye lot tolerances.

Australia Freecall: 1800 136 040
New Zealand Freecall: 0800 445 510

Email: sales@victoriacarpets.com.au
www.victoriacarpets.com.au

UL CERTIFIED ENVIRONMENTAL PRODUCT DECLARATION UL.COM/EPD

VERIFIED hpd VERSION 2.1

CRI THE CARPET AND RUG INSTITUTE

SINGAPORE GREEN BUILDING PRODUCT SGBC LEADER