SPECTRE



PRODUCT SPECIFICATIONS

Product Description Fibre Dye Method Pile Weight Machine Gauge Pile Height Total Thickness Backing Tile Size Installation Method

Textured Loop nexton Premium Nylon with recycled content Solution Dyed 600 g/m² - 18 oz 1/12" High 5 mm to Low 2.5 mm 7.5 mm Recycled Tuntex Duraback 500mm x 500mm Quarter Turn Brick



To be laid in accordance with AS/NZS 2455:2007(Parts 1 & 2)

Adhesive Anti-Static Performance Dimensional Stability Fire Rating (AS/ISO 9239.1:2003) Area of Use Stain Resistance Soil Resistance

ENVIRONMENTAL CREDENTIALS

| Environmental Management System |
|---------------------------------|
| Environmental Accreditation |

Indoor Air Quality

Product Stewardship

Full floor coverage with low VOC pressure sensitive adhesive AATCC 134 < 3.5kV < 0.2%

Critical Radiant Flux 7.5 kW/m² Contract Heavy Duty & Stairs stainShield treatment Soil (GUARD treatment

ISO 14001:2015 certified (IQNet)

Achieves Level 4+ Certification under the ACCS Environmental Classification Scheme

VOC emission rates meet the criteria for the Green Label Plus and the Green Building Council of Australia.

Victoria Carpets, in partnership with our customer, will on a project by project basis, enter into a contractual agreement to take back carpet at the end of its service life for reprocessing, reuse or recycling.

WARRANTIES

15 Years Limited Warranties for Wear, Colourfastness, Anti-Static, Dimensional Stability and Manufacturing Defects

Specifications are subject to and may change without notice. Colour variation may occur between sample and production due to dye lot tolerances.







ISO 9001:2008 ISO 14001:2015 Australia Freecall: 1800 136 040 New Zealand Freecall: 0800 445 510

> Email: sales@victoriacarpets.com.au www.victoriacarpets.com.au www.victoriacarpets.co.nz