

PRODUCT SPECIFICATIONS

Product Description

Textured Loop

Fibre

nexlon™ Premium Nylon with recycled content

Dye Method

Solution Dyed

Pile Weight

600 g/m² - 18 oz

Machine Gauge

1/12"

Pile Height

High 5 mm to Low 2.5 mm

Total Thickness

7.5 mm

Backing


Recycled Tuntex Duraback

Tile Size

500mm x 500mm

Installation Method

Quarter Turn Brick



To be laid in accordance with AS/NZS 2455:2007(Parts 1 & 2)

Adhesive

Full floor coverage with low VOC pressure sensitive adhesive

Anti-Static Performance

AATCC 134 < 3.5kV

Dimensional Stability

< 0.2%

Fire Rating (AS/ISO 9239.1:2003)

Critical Radiant Flux 7.5 kW/m²

Area of Use

Contract Heavy Duty & Stairs

Stain Resistance

stainShield treatment

Soil Resistance

SOIL GUARD treatment

ENVIRONMENTAL CREDENTIALS

Environmental Management System

ISO 14001:2015 certified (IQNet)

Environmental Accreditation

Achieves Level 3 Certification under the ACCS Environmental Classification Scheme

Indoor Air Quality

VOC emission rates meet the criteria for the Green Label Plus and the Green Building Council of Australia.

Product Stewardship

Victoria Carpets, in partnership with our customer, will on a project by project basis, enter into a contractual agreement to take back carpet at the end of its service life for reprocessing, reuse or recycling.

WARRANTIES

15 Years Limited Warranties for Wear, Colourfastness, Anti-Static, Dimensional Stability and Manufacturing Defects

Specifications are subject to and may change without notice. Colour variation may occur between sample and production due to dye lot tolerances.



ISO 9001:2008
ISO 14001:2015

Australia Freecall: 1800 136 040
New Zealand Freecall: 0800 445 510

Email: sales@victoriacarpets.com.au
www.victoriacarpets.com.au