BERMO



PRODUCT SPECIFICATIONS:

| PILE CONTENT: | 100% Advanced Technology Polypropylene (ATP) |
|---------------------------------------|---|
| PILE WEIGHT: | 1870 gm/m ² - 55 oz/yd ² |
| PILE HEIGHT: | 13mm |
| CARPET THICKNESS: | 15mm |
| MACHINE GAUGE: | 2.54mm - 1/10" |
| STITCH RATE: | As required to provide a carpet of total pile mass, pile height and machine gauge as specified. |
| WIDTH: | 3.66 metres |
| PRIMARY BACK: | Heat Stabilised Woven Polypropylene |
| SECONDARY BACK: | Synthetic Don Bac |
| GRADING: | Residential Extra Heavy Duty & Stairs Contract Medium Duty & Stairs |
| RESIDENTIAL WARRANTY: | 15 Year Limited Residential Wear Warranty |
| TOLERANCE: | Manufactured to A.S. 1385 tolerances. |
| INSTALLATION: | To be laid in accordance with AS/NZS 2455.1:2007 Seam sealer must be applied to all seams (prior to joining). |
| SHADING: (Permanent Pile Reversal) | Cut pile carpets have a propensity to shade. This is not a manufacturing fault. Further information can be obtained from the Carpet Institute of Australia. |
| COLOUR VARIATION: | Colour variation may occur between sample and production due to dye lot tolerances. |
| MATERIAL VARIATION: | Product specifications may change without notice due to raw material availability. |
| COUNTRY OF MANUFACTURE: | Australia |