

PLATINUM PLUSH

PRODUCT SPECIFICATIONS:

PILE CONTENT:	80% Wool 20% Synthetic Featuring <i>Texture Loc</i> ®
PILE WEIGHT:	1695 gm/m ² - 50 oz/yd ²
PILE HEIGHT:	10 mm
CARPET THICKNESS:	12 mm
MACHINE GAUGE:	3.175 mm - 1/8"
STITCH RATE:	As required to provide a carpet of total pile mass, pile height and machine gauge as specified.
WIDTH:	3.66 metres
PRIMARY BACK:	Heat Stabilised Woven Polypropylene
SECONDARY BACK:	Woven Jute
FIRE RATING:	AS/ISO 9239.1:2003
CRF VALUE:	4.3 kW/m ² (Conventional installation)
SMOKE DEVELOPMENT RATE:	162 % min (Conventional installation)
GRADING:	Residential Extra Heavy Duty & Stairs Contract Heavy Duty & Stairs
ENVIRONMENTAL ACCREDITATION:	Certified under the ACCS Environmental Classification Scheme
VOC EMISSIONS:	Meets ACCS Environmental Classification Criteria
WARRANTIES:	15 Year Limited Residential Wear Warranty
TOLERANCE:	Manufactured to A.S. 1385 tolerances.
INSTALLATION:	To be laid in accordance with AS/NZS 2455.1:2007 Seam sealer must be applied to all seams (prior to joining).
SHADING: (Permanent Pile Reversal)	Cut pile carpets have a propensity to shade. This is not a manufacturing fault further information can be obtained from the Carpet Institute of Australia leaflet.
COUNTRY OF MANUFACTURE:	Australia