

# RENDELL PLUSH

## PRODUCT SPECIFICATIONS:

<b>PILE CONTENT:</b>	80% Wool, 20% Synthetic Featuring <i>Texture Loc</i> ®
<b>PILE WEIGHT:</b>	1356 gm/m <sup>2</sup> – 40 oz/yd <sup>2</sup>
<b>PILE HEIGHT:</b>	8 mm
<b>CARPET THICKNESS:</b>	10 mm
<b>MACHINE GAUGE:</b>	3.175 mm - 1/8"
<b>STITCH RATE:</b>	As required to provide a carpet of total pile mass, pile height and machine gauge as specified.
<b>WIDTH:</b>	3.66 metres
<b>PRIMARY BACK:</b>	Heat Stabilised Woven Polypropylene
<b>SECONDARY BACK:</b>	Woven Jute
<b>FIRE RATING:</b>	AS/ISO 9239.1:2003
<b>CRF VALUE:</b>	5.3 kW/m <sup>2</sup> (Conventional installation)
<b>SMOKE DEVELOPMENT RATE:</b>	163 % min (Conventional installation)
<b>GRADING:</b>	Residential Extra Heavy Duty & Stairs Contract Medium Duty & Stairs
<b>ENVIRONMENTAL ACCREDITATION:</b>	Achieves Level 3 Certification under the ACCS Environmental Classification Scheme
<b>VOC EMISSIONS:</b>	Meets ACCS Environmental Classification Criteria
<b>WARRANTIES:</b>	15 Year Limited Residential Wear Warranty
<b>TOLERANCE:</b>	Manufactured to A.S. 1385 tolerances.
<b>INSTALLATION:</b>	To be laid in accordance with AS/NZS 2455.1:2007 Seam sealer must be applied to all seams (prior to joining).
<b>SHADING:</b> (Permanent Pile Reversal)	Cut pile carpets have a propensity to shade. This is not a manufacturing fault further information can be obtained from the Carpet Institute of Australia leaflet.
<b>COUNTRY OF MANUFACTURE:</b>	Australia