

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

## **TEST REPORT**

Client : Victoria Carpet Co Pty Ltd 7-29 Gladstone Road Dandenong VIC 3175

		00.000000	
Test Number	:	23-002369	
Issue Date	:	24/07/2023	
Print Date	:	24/07/2023	
Order Number	r :	56573	
			_

 Sample Description
 Clients Ref : "Sonning"

 Loop pile carpet tested on Dunlop Government Red Underlay

 End Use : Flooring

 Nominal Composition : 100% Wool



300133

65117

C Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing Accreditation Numbers: 983, 985, and 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

Chris Campbell





Page 1 of 2

ICHAEL A. JACKSON B.Sc.(Hons)



Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106

1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051 Phone (03) 9371 2400

## **TEST REPORT**

Client :	Victoria Carpet Co Pty Ltd	Test Number :	23-002369
	7-29 Gladstone Road	Issue Date :	24/07/2023
	Dandenong VIC 3175	Print Date :	24/07/2023
		Order Number :	56573

AS ISO 9239.1-2003

## Reaction to Fire Tests for Floorings. Determination of the Burning Behaviour using a Radiant Heat Source

Date of Sample Arrival		19-06-2	023				
Date Tested	24-07-2023						
CHF Value	1	2	3	Mean			
Length	4.9	-	-	- kW/m²			
Width	4.9	4.9	4.9	4.9 kW/m <sup>2</sup>			
Smoke Value	1	2	3	Mean			
Length	129	-	-	- %.min			
Width	140	132	135	136 %.min			

Each specimen was loose laid over Dunlop - Government Red underlay and 6mm thick fibre reinforced cement board and clamped prior to testing.

HF30 not reported as flame out time occurred before 30 minutes.

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BSEN 13238:2010 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

Results in accordance with section 8.4 have not been included in the report. They are available upon request.

300133

65117

C Australian Wool Testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Testing Accreditation Numbers: 983, 985, and 1356

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

Chris Campbell



Machin

Page 2 of 2

CHAEL A. JACKSON B.Sc.(Hons)